

Technical Data

Delta-I 159

The Sygma™ Delta series are perfect for various types of pipe bevelling and end preparation.

The Delta-I 159 has a compact design with a self-centering system enabling a quick and efficient installation of the tool resulting in high accuracy.



Specification

	Delta-IE159	Delta-IP159
Motorization	Electric (Metabo Motor)	Pneumatic
Power Supply	220-220V PH 50/60 Hz	2000l/min & 1.0 MPa
Motor Power	1500W	1HP
Range (ID)	65-159 mm	65-159 mm
Pipe Thickness	<20 mm	<20 mm
Rotation Speed	35r/min	35r/min
Net Weight	25kg	25kg
Gros Weight	35kg	35kg
Case Dimensions	78 x 30 x 30 cm	78 x 30 x 30 cm

Machine Packing List

Bevelling Tool	1
Expansion Block	4 (set)
0° Facing Tool	1
30° Bevelling Tool	1
37.5° Bevelling Tool	1
Allen Key	1
Hexagon Wrench	2
Instruction Manual	1
Case	1

Key Features

- ⦿ Cold Bevelling (doesn't affect pipe material)
- ⦿ Easy set up & operation (plug&play)
- ⦿ Self-centering with high precision
- ⦿ Small work radius
- ⦿ Ratchet tool to adapt feed easily
- ⦿ Light weight and compact design
- ⦿ Multiple Motorisations (Pneumatic & Electrical)

Tool Bits

J type Beveling
V type Beveling
Facing
Inside Beveling

