

Technical Data

Delta-I 30

The Sygma™ Delta series are perfect for various types of pipe bevelling and end preparation.

The Delta-I 30 has a compact design with a self-centering system enabling a quick and efficient installation of the tool resulting in high accuracy.



Specification

	Delta-IE30	Delta-IP30
Motorization	Electric (Metabo Motor)	Pneumatic
Power Supply	220-220V PH 50/60 Hz	2000l/min & 1.0 MPa
Motor Power	1300W	1HP
Range (ID)	18-28 mm	18-28 mm
Pipe Thickness	<15 mm	<15 mm
Rotation Speed	50r/min	50r/min
Net Weight	10kg	10kg
Gros Weight	13kg	13kg
Case Dimensions	57 x 43 x 17 cm	57 x 43 x 17 cm

Machine Packing List

Bevelling Tool	1
Expansion Block	8 (set)
0° Facing Tool	1
30° Bevelling Tool	1
37.5° Bevelling Tool	1
Allen Key	1
Hexagon Wrench	2
Instruction Manual	1
Case	1

Key Features

- ⦿ Cold Bevelling (doesn't affect pipe material)
- ⦿ Easy set up & operation (plug&play)
- ⦿ Self-centering with high precision
- ⦿ Small work radius
- ⦿ Ratchet tool to adapt feed easily
- ⦿ Light weight and compact design
- ⦿ Multiple Motorisations (Pneumatic & Electrical)

Tool Bits

J type Bevelling
V type Bevelling
Facing
Inside Bevelling

